

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

To better serve all of our customers Indium Corporation has generated one MSDS for this single product to be used within the United States as well as internationally. Some of the regulatory information contained within may not be applicable to the customer's individual state or country. See alloy table for product listing.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH TIN AND LEAD

MSDS Number: MSDS-IN 039 Revised Date: 15 MAY 2013

Product Use: INDUSTRIAL USE (mixture) - METAL ALLOYS CONSISTING OF ONLY TIN AND LEAD

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900 nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct. Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Asia-Pacific Operations-Singapore 29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd No. 428 Xinglong Street

Suzhou Industrial Park
Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

CARCINOGEN LISTED IN:

⊗Eye

⊗Inhalation

⊗Skin ⊗Ingestion

NTP

IARC

OSHA

⊗Not Listed

GHS:





Signal Word: Warning

Hazard statement(s)

H302 Harmful if swallowed H315 Causes skin irritation

H335 May cause respiratory irritation

H332 Harmful if inhaled

H351 Suspected of causing cancer (lead)

H360 May damage fertility or the unborn child (lead)

H373 May cause damage to organs through prolonged or repeated exposure (lead)
H400+H413 Very toxic to aquatic life, may cause long lasting harmful effects to aquatic life

EUH201A Warning! Contains lead

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

P501 Dispose of contents by recycling if possible otherwise dispose of via a approved waste handler.

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with powered metal alloy or fume from molten metal may cause irritation. Severe eye

damage may result from hot molten metal being splashed into the eyes. Wear safety glasses and

face shield when working with molten metal.

Ingestion: Ingestion of dust may cause headache, nausea, abdominal pain, fatigue and pain in the legs,

arms and joints. May be harmful.

Inhalation: Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of

fume or dust may cause headache, nausea, abdominal pain, fatigue and pain in the legs, arms

and joints. Inhalation can be harmful.

Skin Contact: Normal handling of solid metal should not cause any adverse health effects.

Hot molten metal may cause burns to the skin. Wear protective equipment when handling molten

metal. Protect skin when grinding/cutting, may cause irritation.

MSDS - IN 039

Chronic: TIN: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure may result in "stannosis" a mild form of pneumoconiosis.

<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

Exposure to metal fumes may cause irritation to the respiratory system. Long term exposure by inhalation to metal fumes may cause illness such as metal fume fever.

Exposure to lead fume may cause harm. Sign of overexposure is anemia.

WARNING: This product contains a chemical known to the State of California to cause cancer and/or

birth defects (or other reproductive harm). (lead)

NOTE: The Indium Corporation does not recommend, manufacturer, market or endorse any of its

products for human consumption.

WARNING: This product contains lead. Lead may be harmful to your health. US Federal law prohibits the

use of leaded solders in making joints or fittings in any private or public water supply system.

Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components % wt CAS Registry #/EINECS#

TIN * 7440-31-5/231-141-8

LEAD * 7439-92-1/231-100-4

DOES NOT CONTAIN ANY EU SUBSTANCES OF VERY HIGH CONCERN (SVHC)

Symbol: X_n Risk Phrases: R20/22, R36/37/38, R33, R40, R48.R50/53, R61

N.E. = Not established * See alloy table

ALLOY TABLE - Mixture

INDALLOY (METAL)	%TIN Sn	%LEAD	RoHS*	LIQUIDUS °C/°F	SOLIDUS °C/°F	DENSITY (gm/cm³)	
106(Sn63)	63	37	NO	183C/361F	183C/361F	8.4	
107	65	35	NO	184C/363F	183C/361F	8.33	
108	70	30	NO	186C/367F	183C/361F	8.16	
109	60	40	NO	191C/376F	183C/361F	8.5	
110	75	25	NO	192C/378F	183C/361F	8.00	
112	80	20	NO	199C/390F	183C/361F	7.85	
113	55	45	NO	200C/392F	183C/361F	8.68	
114	85	15	NO	205C/401F	183C/361F	7.70	
116	50	50	NO	212C/414F	183C/361F	8.87	
118	90	10	NO	213C/415F	183C/361F	7.55	
120	48	52	NO	218C/424F	183C/361F	8.95	
122	95	5	NO	222C/432F	183C/361F	7.42	
125	45	55	NO	227C/441F	183C/361F	9.07	
130	40	60	NO	238C/460F	183C/361F	9.28	
135	35	65	NO	247C/477F	183C/361F	9.50	
141	30	70	NO	257C/495F	183C/361F	9.72	
145	25	75	NO	268C/514F	183C/361F	9.96	
INDALLOY	%TIN	%LEAD	RoHS*	LIQUIDUS	SOLIDUS	DENSITY	
(METAL)	Sn	Pb	Compliance	°C/°F	°C/°F	(gm/cm³)	
149	20	80	NO	280C/536F	183C/361F	10.21	
153	15	85	NO	288C/550F	183C/361F	10.48	
159	10	90	YES	302C/576F	275C/527F	10.75	
171	5	95	YES	312C/594F	308C/586F	11.06	
213	62	38	NO	183C/362F	182.7C/361F	8.43	
242	10.50	89.50	NO	302C/576F	275C/527F	10.75	
Non Standard Alloy Mixture							
Non-Standard	2	98	YES	-	-	8.40	
Non-Standard	3	97	YES	-	-	11.20	
Non-Standard	61.9	38.1	NO	-	-	8.43	

^{*}RoHS = Restriction on Hazardous Substances (Review for any applicable exemptions that may apply)

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established. Massive metal is not flammable; however dust or powder may

be flammable.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions. Never add water to

molten metal.

Special Fire Fighting

Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Contain spill. If molten, cool to allow metal to solidify. If a solid metal, wear gloves, pick

up and return to process. If dust, wear recommended personal protective equipment. DO NOT SWEEP, avoid generation of dust. Ventilation required. Use a vacuum, place in barrels and return to process if applicable. Otherwise, dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations. Metal has

reclaim value.

7. HANDLING AND STORAGE

Handling Only dry metals should be added to molten bath. If working with molten metals, or exposed to

Precautions: fume or dust, use appropriate personal protective equipment.

Storage Precautions: Store product in a cool, dry area away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

		CAS/EINECS#	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
		(Germany)	-	2	<u>-</u>
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	-	0.05	-
		(China)	-	0.05(dust)	-
			-	0.03(fume)	-
		(Mexico)	0.15	-	-
		(Singapore)	0.15	-	-
		(Germany)	-	0.05	-

Symbol: X_n Risk Phrases: R20/22, R36/37/38, R33, R40, R48, R50/53, R61

N.E. = Not established * See alloy table

Lead and Tin: Immediately Dangerous to Life and Health: 100 mg/m³ (Pb)

Engineering Controls: Exhaust ventilation is required to control any air contaminants containing lead. Control

concentration of all components so that their permissible exposure limits are not exceeded.

Personal protection:

Eyes: Chemical safety glasses/goggles and face shield with molten metal.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/dust chemical

cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or if in powder form. Avoid inhalation of lead dust. Additional respiratory protection may

be required based on the work conditions.

Skin: Gloves-leather or impervious (vinyl) type. Heat resistant gloves if handling hot metal. Safety type

boots. Personal protective equipment is recommended when working with molten metal to avoid

burns.

Other: Lab coat, safety shower and eye-wash fountain in work area. Avoid the use of contact lenses in high

fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. **Practices:** Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water

immediately upon leaving the work area. Follow standard lead work practices as established under

governmental regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver grey solid metal **Boiling Point:** Not applicable. Odor: Odorless **Melting Point:** See Table **Specific Gravity:** See Table pH: Not applicable **Vapor Pressure:** Not applicable. Solubility in Water: Insoluble

Vapor Density: (air=1) Not applicable. Flash point: Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization:

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with mineral acids.

Hazardous Decomposition / Harmful organic fumes and toxic oxide fumes may form at elevated

Combustion: temperatures.

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: National Toxicity Program (NTP):

Will not occur.

Occupational Safety & Health Administration (OSHA): No U.N. International Agency for Research on Cancer (IARC): Yes

Lead and Lead compounds are listed as possible carcinogens.

LD50: Not established **LC50**: Not established

Other: Chronic Toxicity: Lead can cause potential harm to the developing fetus.

Irritancy of Product:Not establishedMutagenicity:Not establishedSensitization to Product:Not establishedTeratogenicity:Not establishedReproductive Toxicity:No specific data is availableSynergistic Products:Not established

RTECS#: Lead - OF7525000 RTECS#: Tin - XP7320000 (Registry of Toxic Effects of Chemical Substances)

12. ECOLOGICAL INFORMATION

Product mixture not tested.

Lead – Toxicity to fish – mortality LOEC – rainbow trout – 1.19 mg/l – 96h. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Bioaccumulation – Oncorhynchus kisutch – 2 weeks Bioconcentration factor (BCF): 12. Fresh fish: 0.44 mg/l LC50 96h/ 1.32 mg/l LC50 96h/water Flea: 600 ug/l EC50 = 48h

Avoid release to environment.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations. Avoid

release to the environment.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Not hazardous under shipping modes/ regulations.

UN - none

North American Emergency Guide Book - Not classified

15. REGULATORY INFORMATION

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2A - Materials Causing Other Toxic Effects - Very Toxic Material (Chronic).

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican regulations: NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

California PROP 65(Safe Drinking Water Standard): WARNING: This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (lead)

SARA 313 Listing - 40 CFR 372.65: Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

Most of the ingredients are listed on the Canadian Domestic Substance List.

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

 X_n

MSDS - IN 039

Risk Phrases:

R20/22 Harmful by inhalation and if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin

R33 Danger of cumulative effects (lead)

R40 Limited evidence of carcinogenic effect (lead)

R48 Danger of serious damage to health by prolonged exposure (lead)

R50/53 Very toxic to aquatic environment and may cause long-term adverse effects in the aquatic environment

R61 May cause harm to the unborn child (lead)

Safety Phrases:

S20/21 When using do not eat, drink or smoke

S22 Do not breathe dustS23 Do not breathe fumes

S24/25 Avoid contact with skin and eyes

S27 Take off immediately all contaminated clothing

S28 After contact with skin wash immediately with plenty of soap and water

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label

S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 1 Reactivity: 0

Revised Date: 15 MAY 2013

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. The Indium Corporation does not recommend, manufacturer, market or endorse any of its products for human consumption.